

EF 50MM f/1.8 STM



FOR CREATIVE PORTRAITS & LOW LIGHT PHOTOGRAPHY

The EF 50mm f/1.8 STM excels at portraiture, low-light photography, and adding an artistic edge to everyday objects and settings, thanks to its wide f/1.8 maximum aperture and 50mm focal length



WIDE f/1.8 APERTURE

It's easy to capture superb portraits, or bold, artistic photos and movies with the EF 50mm f/1.8 STM – the wide f/1.8 maximum aperture provides precise control over depth of field. Additionally, this wide aperture lets more light into the lens, so you can comfortably shoot in darker conditions

STEPPING MOTOR TECHNOLOGY (STM)

The EF 50MM f/1.8 STM features stepping motor technology which delivers fast, smooth, and near silent autofocus capability. This is particularly beneficial when shooting movies or shooting in live view mode

COMPACT, LIGHTWEIGHT AND AFFORDABLE

The EF 50MM f/1.8 STM has a compact and lightweight design, weighing a mere 160g, and easily slips into your bag adding very little to the overall weight of your kit. The lens's new design compliments both Canon's consumer and mid-range EOS DSLRs, while the new metal mount provides a more robust connection to camera bodies



no one sees it like you

Canon

EF 50 f/1.8 STM

FOR CREATIVE PORTRAITS & LOW LIGHT PHOTOGRAPHY

3 KEY BENEFITS OF WIDE f/1.8 APERTURE



Significantly blurred backgrounds mean that the main subject of your image really stands out



Movement of fast-moving subjects can be frozen with a wide aperture at fast shutter speeds



In low light situations, handheld shooting is possible without excessively increasing ISO speeds

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS

OPTICAL FEATURES/ SPECIFICATIONS	
Angle of view (horzntl, vertl, diagnl)	40°, 27°, 46°
Lens construction (elements/groups)	6/5
No. of diaphragm blades	7
Minimum aperture	22 (Minimum aperture if using 1/3stop increments)
Closest focussing distance (m)	0.35
Maximum magnification (x)	0.21
Distance Information	Yes
Image stabilizer	-
AF actuator	STM
PHYSICAL SPECIFICATIONS	
Dust/moisture resistance	-
Filter diameter (mm)	49
Max. diameter x length (mm)	69.2 x 39.3
Weight (g)	159
ACCESSORIES	
Lens cap	E-49
Lens hood	ES-68
Lens case/pouch	LP1014
Rear cap	Lens Dust Cap E
Magnification with Extension Tube EF12 II	0.45-0.24
Magnification with Extension Tube EF25 II	0.74-0.53
Extender Compatibility	Not Compatible
Other Accessories	PF49 Protect Filter

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon