

# Eaton 5E2200UIAU

Catalog Number: 5E2200UIAU

Eaton 5E Gen2 UPS USB AU, 2200 VA, 1200 W, Input:cord,  
Outputs: (3) AU, Tower

## General specifications

Product Name	Catalog Number
Eaton 5E Gen2 UPS	5E2200UIAU
Product Length/Depth	Product Height
330 mm	180 mm
Product Width	Product Weight
133 mm	9.8 kg
Compliances	Certifications
RoHS Directive	IEC/EN 62040-3
LVD Directive	IEC/EN 62040-1
Packaging Directive	IEC/EN 62040-2
WEEE Directive	CE
Batteries Directive	EAC
EMC Directive	UKCA
CB	Cm
	Ukr



Special features

Automatic Voltage Regulation (AVR)  
Saves space with a compact tower design  
HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)

Type

UPS

Topology

Line-interactive

Form factor

Tower

Construction type

Free standing model

Color

Black

VA rating

2200 VA

Wattage

1200 W

Rack mounting kit

No

Package contents

Quick start  
Safety instructions

Surge protection

Yes

Internal bypass

No

Hot swap power

No

Auto shutdown function

Yes

Primary frequency - max

65 Hz

Primary frequency - min

45 Hz

Input connection

AU plug

Input nominal voltage

240V

Nominal frequency

50/60 Hz

Input frequency range

45-65 Hz

Receptacle

(3) AU

Number of Outputs C13

3

Voltage

240V

Output nominal voltage

240V

Feed type

1

Voltage type

AC

Runtime graph

[View runtime graph](#)

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Battery rating

12 V / 9 Ah

Battery type

Sealed, lead-acid

Extended battery capability

No

Communication

USB port (HID compliant)

Ethernet interface

No

Includes network card

No

Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

User interface

LEDs

Type of interface

USB

Potential free switch contact

No

Noise level

<40 dB at 1 meter

Relative humidity

0-85% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Operating temperature - max

40 °C

Operating temperature - min

0 °C

Output apparent power

2200 VA

Input voltage - max

300 V

Input voltage - min

140 V

Output voltage - max

257 V

Output voltage - min

195 V

Secondary frequency - max

60 Hz

Secondary frequency - min

50 Hz

Battery quantity

2

Efficiency

95

Input voltage range

140-300 V

Output frequency

50/60 Hz

Output voltage range

195-257 V

Phase (input)

1

Phase (output)

1



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)